



SMARTdesks™ SS Series Product Specs

ISS-603630-CA1 Sit-Stand Lectern Desk with Sub-Surface (19" - 21") Monitor

Materials and Construction Specifications

SS Monitor Window – Flush-mounted, 6mm tempered glass window gray-tinted (40%). Sized to accept up to 21" VDT.

Monitor Shelf – Custom Assembly System™ provides height/depth/angle adjustable monitor support platform under the worksurface offering additional structural strength once fixed at optimum height. Shelf is edge-banded in 3mm PVC to provide a soft, rounded, user-friendly finish.

Convertible CPU Cabinet™ – Right-hand storage/CPU cabinet with one adjustable shelf. Accommodates supplies and equipment or up to two desktop or two mid-tower CPU cases. Locking door.

Tower CPU Bay – Left-hand bay accommodates mid-tower CPU case. Locking door.

Top Surface - 0.048" thick, high-pressure laminate (exceeds performance requirements of NEMA 3-1995 Grade HGS) bonded to 30mm thick 50 lb. medium density particleboard with phenolic resin impregnated backer sheet. All edges are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Base Panels - 0.020" thick melamine coated finish thermally fused to both sides of 19mm thick 47 lb. medium density particleboard. All exposed edges (including bottom edges in contact with the floor - to prevent water damage) are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Articulated Keyboard/Mouse Platform – 3M™ AKT200SL dual-arm keyboard/mouse platforms provide a full range of sit-stand and tilt adjustments. Meets ADA requirements.

Construction – European 32mm woodworking technology employing steel-to-steel pin and cam connections (thru-drilled for full panel integrity) where needed to provide durability, ease of assembly and modularity.

Ventilation – Panels are assembled to permit adequate airflow around components.

Floor Glides - All units are provided with standard adjustable 1¼" steel leveling glides with vinyl shield attached to metal inserts in the vertical support panels. 3/4" height adjustment range.

Desktop Podium - Removable desktop lectern in finish matching base panels is included.

Integral Wire Management™ - Vertical and horizontal wire channeling, 80mm side access grommets are positioned to align with other components and wall power/data access points.

