



SMARTdesks™ DEMI™ Product Specs

SDE-603030-TK9 Single Station Computer Table with Articulated Keyboard/Mouse Platform

Materials and Construction Specifications

Top Surface - 0.048" thick, high-pressure laminate (exceeds performance requirements of NEMA 3-1995 Grade HGS) bonded to 30mm thick 50 lb. medium density particleboard with phenolic resin impregnated backer sheet. All edges are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Keyboard/Mouse Platform – Single-arm, articulated keyboard/mouse platform with swivel, tilt and 6" height range adjustability. Meets ADA requirements for wheelchair accessibility.

Wire Access Grommet – An 80mm diameter wire access grommet with cover is placed in the desk top to channel monitor cables to the CPU bay below the surface.

Tower CPU Bay – Accommodates mid-tower CPU case.

Base Panels - 0.020" thick melamine coated finish thermally fused to both sides of 19mm thick 47 lb. medium density particleboard. All exposed edges (including bottom edges in contact with the floor - to prevent water damage) are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Construction – European 32mm woodworking technology employing steel-to-steel pin and cam connections (thru-drilled for full panel integrity) where needed to provide durability, ease of assembly and modularity.

Ventilation – Panels are assembled to permit adequate airflow around components.

Floor Glides - All units are provided with standard adjustable 1¼" steel leveling glides with vinyl shield attached to metal inserts in the vertical support panels. 3/4" height adjustment range.

Integral Wire Management™ - Vertical cable chase permits access to floor outlets and ganging between pairs of tables.

