



## SMARTdesks™ DEMI™ Product Specs

---

**TDE-783936-xxM Triple Half-Round Computer Table for iMAC® and other Combined VDT/CPUs (Stand-up)**

**Materials and Construction Specifications**

**Top Surface** - 0.048" thick, high-pressure laminate (exceeds performance requirements of NEMA 3-1995 Grade HGS) bonded to 30mm thick 50 lb. medium density particleboard with phenolic resin impregnated backer sheet. All edges are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

**Wire Access Grommet** – An 80mm diameter wire access grommet with cover is placed in the desk top to channel cables below the worksurface.

**Base Panels** - 0.020" thick melamine coated finish thermally fused to both sides of 19mm thick 47 lb. medium density particleboard. All exposed edges (including bottom edges in contact with the floor - to prevent water damage) are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

**Construction** – European 32mm woodworking technology employing steel-to-steel pin and cam connections (thru-drilled for full panel integrity) where needed to provide durability, ease of assembly and modularity.

**Ventilation** – Panels are assembled to permit adequate airflow around components.

**Floor Glides** - All units are provided with standard adjustable 1¼" steel leveling glides with vinyl shield attached to metal inserts in the vertical support panels. 3/4" height adjustment range.

**Integral Wire Management™** - Vertical cable chase permits access to floor outlets and ganging between pairs of tables.

