



## SMARTdesks™ DEMI™ Product Specs

---

### **TDE-844236-CK9 Triple Stand-up Computer Table with Articulated Keyboard/Mouse Platforms**

#### **Materials and Construction Specifications**

**Top Surface** - 0.048" thick, high-pressure laminate (exceeds performance requirements of NEMA 3-1995 Grade HGS) bonded to 30mm thick 50 lb. medium density particleboard with phenolic resin impregnated backer sheet. All edges are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

**Keyboard/Mouse Platforms (3)** – Single-arm, articulated keyboard/mouse platform with swivel, tilt and 6" height range adjustability. Meets ADA requirements for wheelchair accessibility.

**Wire Access Grommet** – An 80mm diameter wire access grommet with cover is placed in the desk top to channel monitor cables to the CPU bay below the surface.

**Convertible CPU Cabinet™** – 28" wide cabinet accommodates three desktop or mid-tower CPU cases. Includes two adjustable shelves.

**Base Panels** - 0.020" thick melamine coated finish thermally fused to both sides of 19mm thick 47 lb. medium density particleboard. All exposed edges (including bottom edges in contact with the floor - to prevent water damage) are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

**Construction** – European 32mm woodworking technology employing steel-to-steel pin and cam connections (thru-drilled for full panel integrity) where needed to provide durability, ease of assembly and modularity.

**Ventilation** – Panels are assembled to permit adequate airflow around components.

**Floor Glides** - All units are provided with standard adjustable 1¼" steel leveling glides with vinyl shield attached to metal inserts in the vertical support panels. 3/4" height adjustment range.

**Integral Wire Management™** - Vertical cable chase permits access to floor outlets and ganging between pairs of tables.

