



SMARTdesks™ DLSeminar™ Product Specs

Leg Series 105 Double Station Seminar Tables

DDL-722028-MC_x - DDL-722428-MC_x - DDL-723028-MC_x - DDL-723628-MC_x

Materials and Construction Specifications

Top Surface - 0.048" thick, high-pressure laminate (exceeds performance requirements of NEMA 3-1995 Grade HGS) bonded to 30mm thick 50 lb. medium density particleboard with phenolic resin impregnated backer sheet. All edges are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Sizes – Top surface available in four depths and may be specified at any width within range by entering the table width in inches as the first two of the six digits in the product number. The second two digits refer to the depth and the third two refer to the height.

Series 105 Leg Set (2) – Available at standard price in 18 stock powder coat finishes.

Base - 1-1/2" x 2" rectangular tubing, 12 gauge steel mainbar with rolled and welded end-caps.

Column - 1-1/2" x 4" rectangular tubing, 12 gauge steel. Column is offset 3" on base to increase leg room.

Mounting Plate - Stamped 7 gauge steel with welded reinforcement.

Levelers - 1" diameter levelers secured in threaded inserts in base.

Anti-Sag Support Beam - 1/2" x 1-1/2" Steel Beam is positioned between the legs to prevent sagging.

Modesty Panel – 10" high (x 1" less than width of top) spaced 1.5" below bottom of worksurface. Mounted on removable hinge mechanism attached to legs.

