



SMARTdesks™ DLSeminar™ Product Specs

Leg Series 101 Double Station Seminar Tables

DDR-602028-xTx - DDR-602428-xTx - DDR-603028-xTx - DDR-603628-xTx

Materials and Construction Specifications

Top Surface - 0.048" thick, high-pressure laminate (exceeds performance requirements of NEMA 3-1995 Grade HGS) bonded to 30mm thick 50 lb. medium density particleboard with phenolic resin impregnated backer sheet. All edges are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Sizes – Top surface available in four depths and may be specified at any width within range by entering the table width in inches as the first two of the six digits in the product number. The second two digits refer to the depth and the third two refer to the height.

Series 101 Leg Set (2) – Available at standard price in 18 stock powder coat finishes.

Base - 2" diameter, 13 gauge steel mainbar with welded end-caps.

Column - 2" diameter, 13 gauge steel. Column is offset 3" on base to improve leg room.

Mounting Plate - Stamped 7 gauge steel, welded reinforcement.

Levelers - 1" diameter levelers secured in threaded inserts in base.

Anti-Sag Support Beam - 1/2" x 1-1/2" Steel Beam is positioned between the legs to prevent sagging.

