



SMARTdesks™ DT Series Product Specs

IDT-723030-CA9 Sit-Stand Lectern/Desk with (14" - 19") Desktop Monitor

Materials and Construction Specifications

Top Surface - 0.048" thick, high-pressure laminate (exceeds performance requirements of NEMA 3-1995 Grade HGS) bonded to 30mm thick 50 lb. medium density particleboard with phenolic resin impregnated backer sheet. All edges are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Wire Access Grommet – An 80mm diameter wire access grommet with cover is placed in the desk top to channel monitor cables to the CPU bay below the surface.

Convertible CPU/Storage Cabinets™ – Two cabinets with one adjustable shelf. Accommodates supplies and equipment or either two desktop or two mid-tower CPU cases. Both with locking doors.

Base Panels - 0.020" thick melamine coated finish thermally fused to both sides of 19mm thick 47 lb. medium density particleboard. All exposed edges (including bottom edges in contact with the floor - to prevent water damage) are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Articulated Keyboard/Mouse Platform – 3M™ AKT200SL dual-arm keyboard/mouse platforms provide a full range of sit-stand and tilt adjustments. Meets ADA requirements.

Desktop Podium - Removable desktop lectern in finish matching base panels is included.

Construction – European 32mm woodworking technology employing steel-to-steel pin and cam connections (thru-drilled for full panel integrity) where needed to provide durability, ease of assembly and modularity.

Ventilation – Panels are assembled to permit adequate airflow around components.

Floor Glides - All units are provided with standard adjustable 1¼" steel leveling glides with vinyl shield attached to metal inserts in the vertical support panels. 3/4" height adjustment range.

Integral Wire Management™ - Vertical and horizontal wire channeling, 80mm side access grommets are positioned to align with other components and wall power/data access points.

