



SMARTdesks™ FP Series Product Specs

TFP-102628-CxF Double Semi-Recessed (15" - 18") LCD Monitor Workstation w/o keyboard tray

Materials and Construction Specifications

SR Monitor Cutouts (3) – With soft vinyl T-mold edges to accommodate recessed monitor. Sized to accept up to 18" Flat Panel Display.

Monitor Shelves (3) – Custom Assembly System™ provides height adjustable monitor support platform offering additional structural strength once fixed in place. Shelves are edge-banded in 3mm PVC to provide a soft, rounded, user-friendly finish.

Convertible CPU Cabinet™ – Centered between center and right-side users with one adjustable shelf. Accommodates three desktop or two mid-tower CPU cases.

Tower CPU Bay – 10" wide bay at right-side of left-side user accommodate mid-tower CPU case.

Top Surface - 0.048" thick, high-pressure laminate (exceeds performance requirements of NEMA 3-1995 Grade HGS) bonded to 30mm thick 50 lb. medium density particleboard with phenolic resin impregnated backer sheet. All edges are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Base Panels - 0.020" thick melamine coated finish thermally fused to both sides of 19mm thick 47 lb. medium density particleboard. All exposed edges (including bottom edges in contact with the floor - to prevent water damage) are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

Construction – European 32mm woodworking technology employing steel-to-steel pin and cam connections (thru-drilled for full panel integrity) where needed to provide durability, ease of assembly and modularity.

Ventilation – Panels are assembled to permit adequate airflow around components.

Floor Glides - All units are provided with standard adjustable 1¼" steel leveling glides with vinyl shield attached to metal inserts in the vertical support panels. 3/4" height adjustment range.

Integral Wire Management™ - Vertical and horizontal wire channeling, 80mm side access grommets are positioned to align with other components and wall power/data access points.

