



**SMARTdesks™ SPEX Component and Equipment Cabinets Product Specs**

**SPX-202426-FDL Storage Pedestal with Locking Door (hinged left)**

**Materials and Construction Specifications**

**Top Surface** - 0.048" thick, high-pressure laminate (exceeds performance requirements of NEMA 3-1995 Grade HGS) bonded to 30mm thick 50lb. medium density particleboard with phenolic resin impregnated backer sheet. All edges are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

**Base Panels** - 0.020" thick melamine coated finish thermally fused to both sides of 19mm thick 47 lb. medium density particleboard. All exposed edges (including bottom edges in contact with the floor - to prevent water damage) are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

**Compatibility** - Designed to fit in 20" wide workstation bay (requires elimination of bottom shelf).

**Locking Door** – Door with cylinder lock and key - hinged left.

**Construction** – European 32mm woodworking technology employing steel-to-steel pin and cam connections (thru-drilled for full panel integrity) where needed to provide durability, ease of assembly and modularity.

**Floor Glides** - All units are provided with standard adjustable 1¼" steel leveling glides with vinyl shield attached to metal inserts in the vertical support panels. ¾" height edjstment range.

**Integral Wire Management™** - Horizontal wire channeling, 80mm side access grommets are positioned to align with other components and wall power/data access points.

