



## SMARTdesks™ MPLEX™ Product Specs

---

### **MFP-602642-LK9 Double Bay Multimedia Lectern with Semi-Recessed (15" - 18") LCD Flat Panel Display**

#### **Materials and Construction Specifications**

**Monitor Cutout (left)** – With soft vinyl T-mold edges to accommodate recessed LCD monitor. Sized to accept up to 18" display.

**Monitor Shelf** – Custom Assembly System™ provides height adjustable monitor support platform offering additional structural strength once fixed in place.

**Main Bay (left)** – Two locking doors permit access to storage area below monitor. Available interior height depends on actual monitor size. Inside is 31.75" wide x 24" deep. Includes (as standard) remote-switched, surge-protected 6-outlet power strip. Power switch is mounted under left side of keyboard.

**Auxiliary Bay (right)** – 26" interior width x 34.75" interior height x 24" interior depth cabinet with one locking door and two adjustable shelves. Integral wire management allows passage of cables between bays and vertically behind shelves.


**Top Surface** - 0.048" thick, high-pressure laminate (exceeds performance requirements of NEMA 3-1995 Grade HGS) bonded to 30mm thick 50 lb. medium density particleboard with phenolic resin impregnated backer sheet. All edges are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

**Base Panels** - 0.020" thick melamine coated finish thermally fused to both sides of 19mm thick 47 lb. medium density particleboard. All exposed edges (including bottom edges in contact with the floor - to prevent water damage) are banded in 3mm thick, color-thru PVC mechanically applied under pressure and heat.

**Keyboard/Mouse Platform** – Pullout platform at 27" above floor match base panel finish and edge trim. Mounted with full-extension ball bearing slides with lifetime warranty.


**Construction** – European 32mm woodworking technology employing steel-to-steel pin and cam connections (thru-drilled for full panel integrity) where needed to provide durability, ease of assembly and modularity.

**Integral Wire Management™** - Vertical and horizontal wire channeling, 80mm side access grommets are positioned to align with other components and wall power/data access points.




TOP

SIDE



FRONT



REAR